AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 🔺 CH-1844 Villeneuve 🔺 +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Flight test report: EN 926-2:2013+A1:2021* & NfL 2-565-20

Manufacturer Sol Paragliders		Certification number		PG_2233.2023		
Address Rua Walter Marquardt, 1180 cp 370 89259-565 Jaraguà do Sul, S.C. Brazil		Flight test	1	7.10.2018		
Glider model Prymus 6 S		Classification	A	Α		
Serial number 20746		Representative	Ν	None		
rimmer no		Place of test	V	/illeneuve		
Folding lines used	no					
Test pilot		Philippe Dupont	C	Claude Thurnheer		
Harness		Dudek - Zero Gravity M	l	Icaro - Energy 2 L		
Harness to risers distance (cm)		43	4	43		
Distance between risers (cm)		40	4	4		
		75	-	90		
Total weight in flight	(~9)	15	9			
1. Inflation/Take-off		Α				
Rising behaviour		Smooth, easy and constant rising	А	Smooth, easy and constant rising	А	
Special take off technique required		No	А	No	А	
2. Landing		Α				
Special landing technique required		No	А	No	Α	
3. Speed in straight flight		А				
Trim speed more than 30 km/h		Yes	А	Yes	A	
Speed range using the controls larger than 10 km/h		Yes	А	Yes	A	
Minimum speed		Less than 25 km/h	А	Less than 25 km/h	A	
4. Control movement		Α				
Max. weight in flight up to						
Symmetric control pressure / travel		Increasing / greater than 55 cm	A	not available	0	
Max. weight in flight 80 kg to 100 kg			•			
Symmetric control pressure / travel		not available	0	Increasing / greater than 60 cm	A	
Max. weight in flight greater than 100 kg			•		•	
Symmetric control pressure / travel 5. Pitch stability exiting accelerated flight		not available	0	not available	0	
	ccelerated flight	A Dive forward less than 30°	۸	Dive forward less than 30°	^	
Dive forward angle on exit		No	A A	No	A	
Collapse occurs 6. Pitch stability operating flight	g controls during accelerated	A	A	NU	A	
Collapse occurs		No	А	No	А	
7. Roll stability and damping		A				
Oscillations	0	Reducing	А	Reducing	А	
8. Stability in gentle spira	ls	Α				
Tendency to return to straight flight		Spontaneous exit	А	Spontaneous exit	А	
9. Behaviour exiting a full	y developed spiral dive	Α				
Initial response of glider (first 180°)		Immediate reduction of rate of turn	А	Immediate reduction of rate of turn	А	
Tendency to return to straight flight		Spontaneous exit (g force decreasing, rate of turn decreasing)	A	Spontaneous exit (g force decreasing, rate of turn decreasing)	A	
Turn angle to recover normal flight		Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A	
10. Symmetric front collar		Α				

*This standard is NOT covered by accreditation D-IS-19457-01 Test Report generated automatically by AIR TURQUOISE SA, valid without signature Rev 07 | 04.03.2022 // ISO | 91.22 // Page 1 of 3

Entry	Rocking back less than 45°	Α	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	A
Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	A	Dive forward 0° to 30° Keeping course	A
Cascade occurs	No	А	No	Α
Folding lines used	No	А	No	Α
At least 50% chord				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	Α
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	А	No	Α
Folding lines used	No	А	No	Α
With accelerator				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
11. Exiting deep stall (parachutal stall)	Α			
Deep stall achieved	Yes	А	Yes	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
Change of course	Changing course less than 45°	А	Changing course less than 45°	А
Cascade occurs	No	А	No	А
12. High angle of attack recovery	A			
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Cascade occurs	No	A	No	Α
13. Recovery from a developed full stall	Α			
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
Collapse	No collapse	A	No collapse	A
Cascade occurs (other than collapses)	No	A	No	A
Rocking back	Less than 45°	A	Less than 45°	A
Line tension	Most lines tight	A	Most lines tight	A
14. Asymmetric collapse	A	~	Woot moo tight	~
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	А	Less than 90° / Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	А	Less than 90° / Dive or roll angle 15° to 45°	А
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	A	Less than 90° / Dive or roll angle 15° to 45°	A

*This standard is NOT covered by accreditation D-IS-19457-01 Test Report generated automatically by AIR TURQUOISE SA, valid without signature Rev 07 | 04.03.2022 // ISO | 91.22 // Page 2 of 3

Re-inflation behaviour Total change of course Collapse on the opposite side occurs Twist occurs Cascade occurs Folding lines used	Spontaneous re-inflation Less than 360° No (or only a small number of collapsed cells with a spontaneous reinflation) No	A A A	Spontaneous re-inflation Less than 360° No (or only a small number of collapsed cells with a spontaneous	A A A
Collapse on the opposite side occurs Twist occurs Cascade occurs Folding lines used	No (or only a small number of collapsed cells with a spontaneous reinflation) No		No (or only a small number of	
Twist occurs Cascade occurs Folding lines used	collapsed cells with a spontaneous reinflation) No	A		A
Cascade occurs Folding lines used			reinflation)	
Folding lines used		А	No	А
	No	А	No	А
	No	А	No	А
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 0° to 15°	A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
15. Directional control with a maintained asymmetric	Α			
collapse				
Able to keep course	Yes	A	Yes	A
180° turn away from the collapsed side possible in 10 s	Yes	A	Yes	A
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency	A			
Spin occurs	No	A	No	A
17. Low speed spin tendency	A			
Spin occurs	No	A	No	A
18. Recovery from a developed spin				
Spin rotation angle after release	Stops spinning in less than 90°	A	Stops spinning in less than 90°	A
Cascade occurs	No	A	No	A
19. B-line stall	A Changing assume loss than 45°	^	Changing as the 45°	•
Change of course before release	Changing course less than 45°	A	Changing course less than 45°	A
Behaviour before release	Remains stable with straight span	A	Remains stable with straight span	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s Dive forward 0° to 30°	A
Dive forward angle on exit	Dive forward 0° to 30°	A		A
Cascade occurs	No	А	No	A
20. Big ears Entry procedure	A Dedicated controls	А	Dedicated controls	А
Behaviour during big ears				
	Stable flight Spontaneous in less than 3 s	A	Stable flight Spontaneous in less than 3 s	A A
Recovery Dive forward angle on exit	Dive forward 0° to 30°	A A	Dive forward 0° to 30°	A
21. Big ears in accelerated flight	A	~	Diversitivate to 50	~
Entry procedure	Dedicated controls	А	Dedicated controls	А
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	A	Stable flight	A
22. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	А	Yes	А
Stall or spin occurs	No	Α	No	A
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0
24. Comments of test pilot				

*This standard is NOT covered by accreditation D-IS-19457-01 Test Report generated automatically by AIR TURQUOISE SA, valid without signature Rev 07 | 04.03.2022 // ISO | 91.22 // Page 3 of 3